Fauteuil de Salon

Jean Prouvé, 1939



Fauteuil de Salon

Fauteuil de Salon joins simple planes into a unified architectural object with a comfortable seat surface and backrest. Rediscovered in the archives of the French engineer Jean Prouvé, the armchair has been updated in a contemporary colour palette. With oiled, solid wood armrests and the designer's characteristic structural aesthetic, the Fauteuil de Salon can

be ideally combined with other pieces in the Prouvé Collection.

Materials

- **Seat and backrest:** polyurethane filling; cover in fabric or leather.
- Seat height: 415 mm (340 mm with applied load, measured in accordance with EN 1335-1).
- Armrests: solid wood with oiled finish; natural oak, smoked oak or American walnut.
- Base: bent sheet steel and tubular steel, powder-coated (smooth).
- **Glides:** hard glides for carpet or felt glides for hard floors.
- Origin of wood: oak (Quercus robur) from Western Europe and/or Poland; American walnut (Juglans nigra) from the USA.

DIMENSIONS




Fauteuil de Salon

info@vitra.com | EN 2020 www.vitra.com/fauteuildesalon

COLOURS AND MATERIALS vitra.



Leather Premium Home/Office, L40



Leather Premium is a relatively smooth cowhide leather with a flat grain and fine top sheen. It is dyed-through and lightly pigmented. The semi-aniline leather is soft to the touch and available in 22 colours.

Material

Semi-aniline nappa leather with a very soft and supple feel

Fastness to light

Type 5

Thickness
Fastness to rubbing

1.1–1.3 mm Grade 4 dry and

wet



info@vitra.com | EN 2020 www.vitra.com/fauteuildesalon

vitra.

Twill Home/Office, F60



The high percentage of natural fibres gives Twill very pleasant tactile qualities and an inviting appearance. Extremely durable with excellent abrasion resistance, it combines the qualities typically found in home furnishings with the demanding requirements of the project sector.

Twill is available in 18 colours.

Material

Weight

Width

30% polyamide,

70% new wool

325 g/m² (9.6 oz/y²)

155 cm +/- 2 cm (61") 100,000 Martin-

dale

Fastness to light

Abrasion resistance

Type 6

Pilling

Fastness to rubbing

Grade 4-5 Grade 4-5 dry

and wet



